

# KVVSS-65A-3XKIT



Tri-sector solution that includes 3 KVVSS-65A-R3-V1 antennas and mounting kit to install them on a pipe

- Suitable for attachment to 3.5-6.5 in or 89-165 mm outer diameter pipe
- Compatible with canister concealment shrouds with inner diameter > 23.5 in (597mm)
- Minimum shroud diameter is the same for all applicable pipe diameters

## General Specifications

<b>Band</b>	Multiband
<b>Performance Note</b>	Outdoor usage
<b>RF Connector Interface</b>	4.3-10 Female
<b>RF Connector Location</b>	Bottom
<b>RF Connector Quantity, high band</b>	12
<b>RF Connector Quantity, mid band</b>	12
<b>RF Connector Quantity, low band</b>	6
<b>RF Connector Quantity, total</b>	30

## Dimensions

**Net Weight, with mounting kit** 107 kg | 235.894 lb

## Electrical Specifications

**Operating Frequency Band** 1695 – 2690 MHz | 3100 – 4200 MHz | 617 – 960 MHz

## Packaging and Weights

<b>Width, packed</b>	601 mm   23.661 in
<b>Depth, packed</b>	1027 mm   40.433 in
<b>Length, packed</b>	1667 mm   65.63 in
<b>Weight, gross</b>	135.5 kg   298.726 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>

# KVVSS-65A-3XKIT

---

ROHS Compliant

UK-ROHS Compliant



## \* Footnotes

**Performance Note** Severe environmental conditions may degrade optimum performance