

# BHD-4MM

---



## Double Block Hanger for 5 - 7 mm fiber cables

### Product Classification

|                      |                                      |
|----------------------|--------------------------------------|
| <b>Product Type</b>  | Hanger kit                           |
| <b>Ordering Note</b> | CommScope® standard product (Global) |

### General Specifications

|                          |   |
|--------------------------|---|
| <b>Cables per Hanger</b> | 2   |
| <b>Color</b>             | Black   |
| <b>Hanger Type</b>       | Double block hanger   |
| <b>Mounting</b>          | Mounting hole clearance for 3/8, 16 UNC or M10 threaded rod |

### Dimensions

|  |                    |
|--|--------------------|
| <b>Maximum Stack Height</b>            | 3                  |
| <b>Height</b>                          | 56.1 mm   2.209 in |
| <b>Width</b>                           | 33 mm   1.299 in   |
| <b>Length</b>                          | 67.1 mm   2.642 in |
| <b>Compatible Cable Diameter Range</b> | 5–7 mm             |
| <b>Compatible Diameter, maximum</b>    | 7 mm   0.276 in    |
| <b>Compatible Diameter, minimum</b>    | 5 mm   0.197 in    |
| <b>Nominal Size</b>                    | 4 mm               |

### Electrical Specifications

|                                    |        |
|------------------------------------|--------|
| <b>Return Loss Effect, maximum</b> | 0.1 dB |
| <b>DTF Effect, maximum</b>         | 0.1 dB |

### Material Specifications

|                      |                    |
|----------------------|--------------------|
| <b>Material Type</b> | Engineered plastic |
|----------------------|--------------------|

# BHD-4MM

---

## Environmental Specifications

|   |  |
|---|--|
| <b>Operating Temperature</b>                      | -40 °C to +85 °C (-40 °F to +185 °F)               |
| <b>Environmental Strength Capability</b>          | Double cable weight                                |
| <b>UV Resistance, minimum with no degradation</b> | ≥100 hours exposure in accelerated UV life chamber |

## Packaging and Weights

|                           |                    |
|---------------------------|--------------------|
| <b>Height, packed</b>     | 5.7 cm   2.244 in  |
| <b>Width, packed</b>      | 17.8 cm   7.008 in |
| <b>Length, packed</b>     | 25.4 cm   10 in    |
| <b>Packaging quantity</b> | 10                 |
| <b>Weight, gross</b>      | 0.6 kg   1.323 lb  |

## Regulatory Compliance/Certifications

| <b>Agency</b> | <b>Classification</b>  |
|---------------|--|
| CHINA-ROHS    | Below maximum concentration value  |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system   |
| REACH-SVHC    | Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a> |
| ROHS          | Compliant  |
| UK-ROHS       | Compliant  |



## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power