


# 760018838 | 12 FIBER BREAKOUT KIT

---



12 Fiber Breakout Kit, loose tube

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America
<b>Portfolio</b>	SYSTIMAX®
<b>Product Type</b>	Fiber breakout kit, rectangular

## General Specifications

<b>Color</b>	Black
<b>Compatible Interface</b>	LC   LC, keyed   SC   ST

## Dimensions

<b>Height</b>	7.62 mm   0.3 in
<b>Width</b>	17.78 mm   0.7 in
<b>Length</b>	43.18 mm   1.7 in
<b>Tube Length</b>	609.6 mm   24 in
<b>Tube Inner Diameter</b>	500 µm
<b>Tube Outer Diameter</b>	900 µm

## Material Specifications

<b>Material Type, body</b>	Acrylonitrile butadiene styrene (ABS)
<b>Material Type, tubing</b>	Thermoplastic elastomer (TPE)

## Environmental Specifications

<b>Operating Temperature</b>	-10 °C to +60 °C (+14 °F to +140 °F)
------------------------------	--------------------------------------

## Packaging and Weights

<b>Included</b>	Breakout unit   Instruction sheet   Snap together housing   Twelve buffer tubes, 24 in x 900 µm
<b>Packaging quantity</b>	1

# 760018838 | 12 FIBER BREAKOUT KIT

---

## Regulatory Compliance/Certifications

### Agency

CHINA-ROHS

ISO 9001:2015

REACH-SVHC

ROHS

### Classification

Below maximum concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on [www.commscope.com/ProductCompliance](http://www.commscope.com/ProductCompliance)

Compliant

